



ITEM	DWG. NO	NAME	QTY	MAT'L & SPEC	REMARK
44	BL9242-60-02	套管 Tube		Φ8*Φ10*50	
43	BL9242-60-02	内配线 Lead wire			
42	BL9242-60-01	电源线 Power cord	1	H05VVH2-F 2*0.75mm <sup>2</sup>	
41	XB9008-40-04	胶脚 Foot	4	橡胶	借用XB9008
40	BL9242-10-01	螺钉 Screw	4	ST3*12/十字槽平圆头/镍白锌/A	
39	BL9242-10-01	底座 Base	1	ABS 750SW	
38	HMB48-1-09	压线码 Strain relief	1	PA66 A45-L-1	借用HMB48
37	BL9242-20-01	中大身 Middle body	1	SUS304 TO.6	
36	XB9168V-40-01	马达垫 Motor mat	1	橡胶	借用XB9168V
35	BL9242-60-03	电机 Mtor	1	88/35 650W	
34	XB9168-40-12	马达防震圈 Mtor_retainer	1	Φ30 × Φ14.5 × 7	借用XB9168
33	BL9822-10-08	安全开关支架Safe switch retainer	1	ABS 750SW	
32		微动开关 Micro switch	1	250V/5A/常开(薄片长17.4)	
31	XB9058V-80-01	压缩弹簧 Spring	1	Φ0.4*Φ6.0*12.5/F=1.5/60Mn	借
30	BL9242-10-06	安全开关连杆Safe switch lever	1	ABS 750SW	借用XB91088V
29	XB9008-80-10	定位垫圈 Self locking washer	1	Φ2.7*Φ.6*0.3/65Mn/发黑	借用XB9008
28	XB9008-80-09	扭簧 Wring spring	1	Φ0.8/65Mn(发黑)	借用XB9008
27	BL9242-10-09	档位顶杆 Shift eject pole	1	ABS 750SW	
26	BL9242-10-07	开关旋钮-1 Switch knob-1	1	ABS 750SW	
25	BL9242-10-08	开关旋钮 Switch knob	1	ABS 750SW	
24	BL9242-80-01	档位弹簧 Spring	1	Φ0.3*Φ2.2*6	
23	BL9242-10-04	开关连杆 Switch lever	1	ABS 750SW	
22	XB9008-10-09	开关凸轮 Switch cam	1	PA66+GF30%	借用XB9008
21		螺钉 Screw	8	ST3*10/十字槽平圆头/镍白锌/A	
20		PCB	1		
19	BL9242-10-05	PCB支架 PCB bracket	1	PA66+GF30%	
18	BL9242-10-02	大身 Body	1	ABS PA-757(+)	
17	XB9118-40-07	下连接头 Lower_connector	1	橡胶+镍件	借用XB9118
16	XB9118-40-06	上连接头 Top connector	1	橡胶+镍件	借用XB9118
15		平垫圈 Washer	1	Φ8.2 × Φ13 × 0.8 / 电木	
14		螺钉 Screw	1	ST3*10/十字沉头/不锈钢/A	
13	BL91556G-10-03	安全开关支架-1 Safe switch bracket-1	1	PC2858	借用XB9156G
12	BL91556G-10-02	安全开关连杆Safe switch linker	1	PC2858	借用XB9156G
11	BL9155-80-01	安全开关弹簧Safe switch spring	1	Φ0.6/SUS301	借用XB9155
10	BL91556G-10-01	杯座 Jar base	1	ABS 750SW	借用XB9156G
9	BL9126-40-01	密封圈 Seal	1	硅胶	借用XB9126
8	BL91166G-80-02	搅拌刀轴承 Bearing	1	铜基粉末冶金+耐磨粉	借用XB9116G
7	BL9126-20-01	轴承支架 Oil bearing bracket	1	SUS304	借用XB9126
6	BL9188-40-04	刀轴密封圈 Blade assm ring	1	ABS 750SW	借用XB9188
5	BL9155-80-02	刀组件 Blade assmly	1	SUS301+SUS304	借用XB9155
4	XB9116G-80-03	玻璃杯 Jar	1	玻璃	借用XB9116G
3	BL9242-40-01	杯盖密封圈 Jar cover ring	1	ABS 750SW	
2	BL9242-10-03	杯盖 Jar cover	1	ABS 750SW	
1	XB9198B-10-03	量杯 Measuring	1	AS 335	借用XB9198B

**GUANGDONG XINBAO ELECTRICAL APPLIANCES HOLDINGS CO., LTD.**

MODEL: BL9242(GS) Assemble DWG. NO: XB9242-00-10 REV: A  
 TITLE: 爆炸图 Exploded drawing PREPARED BY: DATE:  
 SCALE: CHECKED BY: DATE:  
 SHEET: 1 of 1 STANDARD BY: DATE:  
 UNITS: mm REVIEWED BY: DATE:  
 FRAME: A1 APPROVED BY: DATE:

技术要求:  
 1.额定电压: 220-240V 50Hz;  
 2.额定功率: 650W;  
 3.大杯容量: 1500ml;  
 4.空载最高转速、距离1米处的噪音不大于90dB;