



技术要求:
 1. 电压为220-240V, 频率为50Hz, 功率780-925W;
 2. 水泵压力为15bar;
 3. 外露部分颜色按客户要求;
 4. 各贴合面配合良好, 止口均匀度依检验标准;
 5. 各部分丝印应清晰、正确、牢固;
 6. 各五金件不得锈蚀, 电镀表面光亮均匀且无脱落和破损划伤等痕迹。

型号: CM4600E-GS 咖啡机 COFFEE MAKER	图号: CM4600E-GS-00-20	版次: A
名称: 爆炸图 Exploded drawing	设计: _____	日期: _____
比例: /	校对: _____	日期: _____
单位: mm	幅面: A2	日期: _____
共 2 张 第 1 张	审核: _____	日期: _____

广东新宝电器股份有限公司

87	CM4600F-GS-10-01	漏斗手柄下盖 handle cover down	1	PP		40	椭圆翘板开关2 Rocker switch	2	250 (125) V/6 (10) A	
86	CM4659-40-05	防水密封圈 waterproof seal ringside	1	硅胶		39	椭圆翘板开关2 Rocker switch	1	250 (125) V/6 (10) A.点动	
85	CM4600E-GS-10-02	漏斗手柄上盖 handle cover up	1	PP		38	顶盖 Top Cover	1	PP	
84	CM4600E-GS-10-03	高压漏斗压钩 Funnel Hook	1	PA6		37	蒸汽阀体 Steam valve body	1	PPS	
83	CM4600E-GS-30-01	高压漏斗 Pressurized funnel	1	铝 DL103		36	机制螺钉 Screw	1	M3×8/一字槽平圆头/B/碳钢/镀蓝白锌	
82	CM4600E-GS-01-01	两杯双层金属滤网 Two cup filter	1	t=0.5/SUS304/两个凸点		35	蒸汽旋钮 Steam button	1	PP	
81	XQ4623-80-17	出水螺钉 Water tube bolt	1	铝 A6063		34	接水盘 Drip tray	1	PP	
80	XQ4623-20-05	过滤片 Filter piece	1	t=0.5/SUS304		33	杯垫 Drip plate	1	铝	
79	CM4640-20-55	出水弹簧 spring	1	Φ0.8×Φ6.6×21.2/SUS304		32	接头 Coupler	1	PP	
78	XQ4623-40-16	出水胶塞 Outlet plunger	1	硅胶		31	接头密封圈 Seal ring	1	硅胶	
77	CM4600-30-03	发热煲固定架 boiler bracket	1	铝 DL103		30	单向阀 Anti-back valve	1	PP	
76	CM4600-40-04	漏斗密封圈 Seal Ring	1	硅胶		29	单向阀弹簧 Spring	1	SUS304	
75	CM4600-30-02	发热煲下盖 Boiler lower cover	1	铝 DL103		28	单向阀密封圈 Anti-back valve seal ring	1	硅胶	
74	CM4600-40-03	发热煲密封圈 Boiler seal ring	1	硅胶		27	水箱 Water Tank	1	PP	
73		自攻螺钉 Screw	1	ST3×10/一字槽/平圆头/RT/碳钢加厚/镀镍		26	水箱提手 Water tank handle	1	PP	
72		弹簧垫圈 spring washer	4	Φ6.1×Φ10.1×1.3/弹簧钢/镀白锌		25	水箱盖 Water tank cover	1	PP	
71		机制螺钉 Screw	4	M6×20/内六角/圆柱头/B/碳钢/镀蓝白锌		24	电源板组件 Power PCB asm	1	CM4600L(GS)/自动断电	
70	CM4600-60-03	发热管 Heat element	1	CM4600_230V/800W/马蹄形		23	水泵支架 Pump bracket	1	PA66	
69	CM4622C-GS-30-01	发热煲上盖 Boiler cover up	1	铝 DL103		22	硅胶管 Silicon tube	1	Φ3.8×Φ8.2×300/透明	
68	CM4600-20-07	固定片 Stator	1	t=1.0/SUS430		21	硅胶管 Silicon tube	1	Φ7×Φ3.8×35/透明	
67	CM4600-80-06	螺母 Nut	1	G1/8/铝6063		20	三通管 Three outlet conduit	1	PA66	
66		喉夹 Clamp	2	Φ8.0×Φ1.2/弹簧钢丝/镀镍(双圈)		19	硅胶管 Silicon tube	1	Φ7×Φ3.8×80/透明	
65	CM4600-80-04	三通接头Connector	1	铝 A6063		18	卡口夹 Clip	1	SUS304	
64	XQ4623-40-14	蒸汽密封垫 Seal ring	1	硅胶		17	转换开关进水管组件 Switch in tube asm	1	Φ2.0×Φ4.0×120	
63	CM4600-80-03	蒸汽调节阀 Steam adjust shaft	1	铝 A6063		16	接头密封圈 Connector Seal ring	5	硅胶	
62	CM4803-40-30	水泵接头密封圈 Seal ring 13	2	硅胶		15	蒸汽胶管 Silicon tube	2	Φ3.8×Φ8.2×150/透明	
61		温控器 Thermostat	1	KSD301/95°C/250V/10A		14	喉夹 Throat clip	1	Φ9.0×Φ1.0/弹簧钢丝/镀镍/双圈	
60	CM4676-20-03	压板2 Press plate 2	1	SGCC/t=2		13	水泵缓冲块1 Pump buffer 1	1	CM4661/橡胶/邵氏硬度70-75(白色)	
59	CM4622-20-03	保险丝夹 Fuse clip	1	9.0×24.0×1.0/SECC		12	水泵缓冲块2 pump buffer	1	CM4661/橡胶/邵氏硬度40-45	
58		自攻螺钉 Screw	6	ST3×6/一字槽/平圆头/B/碳钢/镀蓝白锌		11	水泵 pump	1	P500U 220-240V/50Hz/53W	
57		温控器 Thermostat	1	KSD301/125°C/250V/10A		10	水泵阀门 Pump valve	1	S2	
56	CM4600-40-01	胶脚 Foot	4	硅胶		9	蒸汽调节阀密封圈 Seal ring	3	硅胶	
55	CM4600-10-10	底座 Bottom cover	1	PP		8	CM4803-10-15	1	PA66	
54	CM4622-10-25	压线码 Strain relief	1	PP		7	CM4803-10-15	1	PA66	
53		自攻螺钉 Screw	15	ST3×12/一字槽/平圆头/A/镀蓝白锌		6	CM4602-40-01	1	硅胶	
52	CM4600-10-09	支撑架 Support bracket	1	PP		5	CM4602-10-21	1	PA66	
51	CM4637I-GS-10-01	蒸汽管护套 Steam conduit sleeve	1	PA6		4	CM4803-80-08	1	SUS304	
50	CM4600-10-01	主体 Main housing	1	PP		3	CM4803-40-02	1	硅胶	
49	CM4637I-GS-80-01	蒸汽管 Steam conduit	1	CM4637I-GS		2	CM4803-10-16	1	PA66	
48	XQ4693-20-04	卡圈 Clip of steam pipe	1	t=1.0/SUS304		1	CM4803-10-17	1	PA66	
47		自攻螺钉 Screw	3	ST3×10/一字槽/平圆头/A/不锈钢						
46	CM4622-10-20	咖啡勺 Coffee spoon	1	PP						
45		自攻螺钉 Screw	17	ST3×10/一字槽/平圆头/A/镀蓝白锌						
44		自攻螺钉 Screw	5	ST3×12/一字槽/平圆头/A/镀蓝白锌						
43	CM4600-10-03	发热煲支架 Boiler support	1	PA66						
42		自攻螺钉 Screw	1	ST2.6×8/一字槽/平圆头/A/镀蓝白锌						
41	CM4600-10-14	灯罩 Lamp cover	1	PC						
89		机制螺钉 Screw	2	M4×10/一字槽/平圆头/B/不锈钢						
88		自攻螺钉 Screw	1	ST3×12/一字槽/平圆头/A/不锈钢						